



## BONDING GUTTERS®

30 YEAR GUARANTEE

The GRP Bonding Gutters® create a weather-tight joint between dissimilar roof coverings on semi-detached and terrace homes whether it be new build or refurbishment. Available in two dry fix options and one for traditional mortar bedding.



### FEATURES AND BENEFITS

- The flat and narrow profiles minimise the disturbance to adjoining roof
- Robust weather protection design with twin water bars on each side
- The dry fix options provide a neat finish to the edges of different roof coverings that may be at different heights
- Dry fix products eliminate the mortar installation and maintenance issues
- Up to half the cost and time of traditional lead
- Light in weight and easy to handle
- UV Resistant
- No harmful run-off or staining

### APPLICATION




The Bonding Gutters® should be placed to allow the slate or tile bond to be maintained and using either a replacement tile and a half or wider slate if possible. Designed to fix directly over the tiling or slating battens.

When joining lengths, use the minimum lengths of overlap as follows:

| ROOF PITCH | OVER 39° | 30° - 39° | 22.5° - 29° | BELOW 22.5° |
|------------|----------|-----------|-------------|-------------|
| OVERLAP    | 150mm    | 200mm     | 300mm       | 350mm       |

Minimum roof pitch 17.5°.

### PRODUCT CODES, DIMENSIONS AND COMPATIBILITY


|                                                                                                         |                                                                                                                                                                                              |
|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DRY FIX</b><br>   | <b>Product code:</b> HDL DBG1<br><b>Central Upstand:</b> 70mm<br><b>Dimensions:</b> W 210 x L 3000mm<br><br>To suit slates, flat interlocking and plain tiles.                               |
| <b>DRY FIX</b><br>  | <b>Product code:</b> HDL DBG2<br><b>Central Upstand:</b> 100mm<br><b>Dimensions:</b> W 210 x L 3000mm<br><br>To suit profiled tiles on one or both sides and also typical Scottish practice. |
| <b>MORTARED</b><br> | <b>Product code:</b> HDL BG<br><b>Dimensions:</b> W 225 x L 3000mm<br><br>Traditional option with integral mortar bonding strip, suitable for all applications                               |

### MATERIAL AND COLOUR

GRP and Anthracite



### RELATED PRODUCTS

|                                                                                      |                                                                                                                                                                                                 |
|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>Dry Fix GRP Valley Troughs</b><br>Provides a secure and discreet drainage for inclined roof valleys. Mortarless application and available in three profiles, codes: HDL DVT, DVLPT, DVS      |
|  | <b>CON6+ Universal Ridge and Hip System</b><br>Includes a ventilated membrane with broad corrugated adhesive strips, uni-ridge gaskets, stainless steel straps and fixing screws, code: HD CON6 |
|  | <b>Vapour Permeable Roofing Underlay</b><br>Available in various weights<br>Integral lap tape options<br>Widths of 1.0m or 1.5m                                                                 |